

LIFEGAIN CU-HD1

(Multifunction Defibrillator / Monitor)

Someone goes down in cardiac arrest, resuscitation is just a hand away...

Made in Korea

Key Features

- Efficient and *e-cube* Biphasic Biphasic technology (BTE Type)
- Manual and AED operation
- Defibrillation using paddles, pads or internal paddles
- ECG Monitoring (3-Lead ECG / 5-Lead ECG / 10-Lead ECG)
- SpO₂ pulse oximetry with alarms (Nellcor)
- Noninvasive pacing mode
- NIBP (Non-Invasive Blood Pressure)

Specifications

Display

- LCD Dimensions : 7 inch Diagonal (152mm * 91mm)
- Type : TFT Color
- Resolution : 800 * 480 pixels

Defibrillation

Defib Common

- Waveform : Truncated Exponential Biphasic (e-cube)
- Charge Time : Adapter : Less than 5 seconds to 200 Joules
Battery : Less than 7 seconds to 200 Joules

AED Mode

- Output Energy : 200J
- Shock Delivery : Via multifunction defib electrode pads
- AED Develop Guideline : Shock advisory sensitivity and Specificity meet AAMI DF-80 guidelines
- Voice & Text Prompts : Guide the user through the protocol via multifunction defib electrode pads

Manual Mode

- Output Energy : 1-10J, 15J, 20J, 30J, 50J, 70J, 100J, 120J, (Selected) 150J, 170J, 200J
- Shock Delivery : External paddle (with Pediatric) / Internal paddle
- Synchronous Cardioversion

Printer

- Continuous ECG Strip : Real-Time (8 seconds delay)
- Auto Printing : Recorder can be configured to print marked event, charge, shock and alarms
- Printing Speed : 25mm/s
- Paper : 50mm Width / 40mm Diameters

Automatic Self-Test

- Power On Self-Test
- Run Time Self-Test
- Manual Self-Test
- Periodic Self-Test (Daily / Weekly / Monthly)

Data Storage

- External memory card
- SD Card (ECG data, Event, Voice)

Power Source

External Battery Pack : Lithium Polymer

- Type : 14.8V 3.1Ah (Rechargeable)
- Capacity : When new, minimum of 100 shock deliveries (200J)

AC Power Pack

- Output : 18V, 6A

Noninvasive Pacing

- Waveform : Monophasic Truncated Exponential
- Mode : Demand and Fixed Mode
- Amplitude Accuracy : 0 ~ 200mA (±5mA)
- Pulse Width : 20ms (±1.5%)
- Pulse Rate : 30 ~ 180ppm (±1.5%)
- Refractory Period : 340 msec (30 to 80 ppm)
240 msec (90 to 180 ppm)

SpO₂ Pulse Oximetry

- Saturation : 70 ~ 100% (±3digits)
- Pulse Rate : 20 ~ 250 bpm (±3bpm)
- Perfusion : 0.2%
- Module Manufacturer : Nellcor
- SpO₂ Alarm : Less than Minimum setting rate
Over than Maximum setting rate

NIBP

- Patient Population : Adult, Pediatric, Neonate
- Method : Oscillometric
- Control : Automatic and manual measurements
- Auto Intervals : 1, 3, 5, 10, 15, 30, 60, 120 min
- Displayed Pressures : Systolic, Diastolic, MeanmmHg
- Displayer Units : Adult : 40 to 260 mmHg
Pediatric : 40 to 160 mmHg
Neonate : 40 to 130 mmHg
- Systolic Range : Adult : 20 to 200 mmHg
Pediatric : 20 to 120 mmHg
Neonate : 20 to 100 mmHg
- Diastolic Range : ±3mmHg
- Pressure Transducer : Adult : 300 mmHg
Accuracy Pediatric : 300 mmHg
Neonate : 150 mmHg
- Redundant Circuit Overpressure Limit

ECG Monitoring

- Input : 3-Lead Cable : I, II, III
5-Lead Cable : I, II, III, aVR, aVL, aVF or V
10-Lead Cable : I, II, III, aVR, aVL, aVF or V1, V2, V3, V4, V5, V6
(Display View : All 12-Lead ECG waves display simultaneously)
- Lead Fault : "Lead Fault" message and dashed line display, if an electrode or lead wire becomes disconnected
- Heart Rate Display : 30 to 300 bpm (±3bpm)
- ECG Size : 5, 10, 20mm/mV and Auto-gain
- Heart Rate/Arrhythmia Alarm : HR, Asystole, VF, VT



• Size : 318 × 208 × 355 (W × L × H, mm)
• Weight : 5kg (with external paddle)

Parts & Accessories

Standard Package	Option
- Device	- Carrying case
- External Paddle (Adult, Pediatric)	- SD card
- 3 Lead ECG cable	- SD card reader
- ECG electrodes	- Pediatric pads
- Defi pads & Adaptor	- 5 Lead ECG cable
- Built in printer	- Car cigar lighter jack
- Power cord & SMPS	- SpO ₂ Module Set
- Internal Battery	- Pacer
- Gel	- 10 Lead ECG cable
- User's Guide	- NIBP (Non-Invasive Blood Pressure)
	- Software for data management (CU-EX2)